

S:\Eng\Projects\Parks\Cedar Field Project\Cedar Field - Grading.dwg



CONSTRUCTION NOTES

1. ANTICIPATED CUT QUANTITY = 1000 YD²
2. ANTICIPATED FILL QUANTITY = 1000 YD²
3. THE PROPOSED FIELD SURFACE IS AN ARTIFICIAL GRASS SURFACE
4. ALL EXISTING WOOD LIGHT POLES WILL BE REMOVED AND REPLACED WITH 60' METAL POLES WITH ATTACHED L.E.D. LIGHTING.
5. ALL FENCING SURROUNDING THE BASEBALL FIELD WILL BE REMOVED AND REPLACED WITH SIMILAR FENCING.
6. A 12" CONCRETE CURB APRON WILL BE INSTALLED TO SERVE AS AN ATTACHMENT POINT FOR THE NEW ARTIFICIAL GRASS SURFACE, AND A FOUNDATION FOR THE PROPOSED CHAIN LINK FENCING.
7. AN 8" PVC DRAINAGE SYSTEM WILL BE INSTALLED UNDER THE ATHLETIC SURFACING. DRAINAGE PLANS MAY CHANGE DUE TO MANUFACTURERS SPECIFICATIONS/DESIGN. IT IS ANTICIPATED THAT THE SURFACE WILL BE 100% INFILTRATION.



CALL BEFORE YOU DIG
1-800-424-5555



ELEVATION DATUM IS NAVD 1988

REVISIONS	DATE	DESIGN BY: JASON CANTU	10/24/2019
1.		ENGINEERING CHECKER:	
2.		CONSTRUCTION SUPERVISOR:	
3.		OPERATIONS MANAGER:	
4.		P.W. SUPERINTENDENT:	

EXAMINED AND APPROVED FOR CONSTRUCTION ON THIS _____ DAY OF _____, 2019
BY: JEFF LAYCOCK, PE, CITY ENGINEER
CITY OF MARYSVILLE DEPARTMENT OF PUBLIC WORKS
ENGINEER'S STAMP

CITY OF MARYSVILLE
PUBLIC WORKS DEPARTMENT
80 COLUMBIA AVE MARYSVILLE, WA 98270 (360) 363-8100
Cedar Field
Athletic Surfacing and lighting project
Grading/Fill Area

HOR SCALE 1:20
VER SCALE
DWG. NO. 1
SHEET 1 of 1

